

SENSING **FOR BUILDING** **APPLICATIONS**

Sensor Selection Guide

Honeywell

PRECISION AND VERSATILITY YOU CAN RELY ON

Your source for every job: Honeywell sensors are built to work reliably and install easily, with options to cover all your control applications and mounting options.

TEMPERATURE SENSORS

Support a range of applications from averaging, outdoor and immersion sensors to duct-mount, strap-on and wall mount sensors



CURRENT SENSORS AND SWITCHES

Compatible with building management system, DDC, or PLC controllers



Facilitates proactive fault detection or fail-safe operation to minimize equipment down-time or associated cost

Split core versions for simplified installation in existing applications

HUMIDITY SENSORS

Highly accurate, stable humidity sensors designed for use with HVAC controllers and direct digital controllers (DDCs)



Multiple configurations available, including wall, duct and outdoor

DIFFERENTIAL PRESSURE SENSORS

Field selectable pressure ranges

Analog voltage or current outputs

Dry pressure sensors for building (zone) pressure, filter condition measurement and duct/static applications



Wet pressure sensors for hot/chilled water applications, process control systems, and hydronic system monitoring

IAQ SENSORS

Proper air cleaning and exchange can help reduce disease transmission by removing or dispelling pathogens, as well as odors, chemicals, and CO2

Honeywell CO2, TVOC, PM 2.5 and Multi-Sensors can be combined with the Healthy Buildings dashboard for IAQ monitoring and support demand ventilation control



ECONOMIZER SENSORS

Duct mounted sensors for enthalpy or temperature measurement

Simplifies integration with industry leading Honeywell JADE economizer control for energy savings and improved indoor air quality



WALL MODULES

Simple two-wire connectivity via Sylk™ Bus with up to 3 sensor types per device, plus user interface.



DEW POINT SENSORS

Designed for use in monitoring cooling water pipes or chilled surfaces to determine if temperatures are approaching dewpoint

Suitable for mounting on flat and round surfaces









REASSURE OCCUPANTS THAT YOUR BUILDING IS MEASURABLY SAFER

Honeywell Sensors support a healthier building strategy by enabling facilities to become safer for occupants. Buildings of the future need reliable data to control indoor air quality - and that starts with our versatile range of sensors.

CONTROLLER-SPECIFIC WALL MODULES & TEMPERATURE SENSORS

	Part Number	Images	Display	On-Board Sensors			Features	Customizable Parameters*	Schedule Access	Controller Compatibility
				Temp	Humidity	CO ₂				
Sylk-Enabled Zio Wall Modules	TR120		Yes	✓			Color Touchscreen Temp. Override, Setpoint, Fan	✓	✓	Stryker Spyder Classic Spyder Model 5 CIPer Model 30
	TR120-H			✓	✓			✓	✓	
	TR75		Yes	✓			Temp. Override, Setpoint, Fan	✓	✓	
	TR75-H			✓	✓			✓	✓	
	TR71			✓				✓		
	TR71-H			✓	✓			✓		
	TR42		Yes	✓			Temp. Override, Setpoint, Fan	N/A	N/A	Spyder Classic Spyder Model 5 CIPer Model 30
	TR42-H			✓	✓					
	TR42-CO2			✓		✓				
	TR40		No				No Interface	N/A	N/A	
	TR40-H			✓	✓					
	TR40-CO2			✓		✓				
	TR40-H-CO2			✓	✓	✓				

*For accessing virtually any point in the controller, balancing from wall module, etc.

	Model Number		Sensor Element Type	Sensor Type		Selectable Setpoint Adjustment 55° to 85°F, 13° to 30°C or Relative (- to +)	Occupied Override	LON Jack	Fan Switching	Comments	
	Honeywell Wall Module Model	Replaces Honeywell Model		Temp	Humidity						
Temperature, Humidity and Override Control	TR21	T7770A1006	20K ohms non-linear	✓							
	TR21-A	T7770A3002	10K ohms non-linear for averaging only	✓							
	TR21-H	N/A	20K ohms non-linear	✓	✓			✓			
	TR21-J	T7770A2004		✓				✓			
	TR22	T7770B1004 T7770B1020 T7770B1046		✓		✓		✓			
	TR23	T7770C1002 T7770C1028 T7770C1044		✓		✓		✓	✓		
	TR23-H	N/A		✓	✓	✓		✓	✓		
	TR23-KL	N/A		✓		✓		✓	✓	Knobs not included	
	TR23-H-KL	N/A		✓	✓	✓		✓	✓		
	TR23-N	T7770C1051		✓		✓		✓	✓	No Honeywell logo	
	TR24	T7770D1000		✓				✓	✓		
	TR22-F5	N/A		✓		✓			✓	5 position	
	TR23-F3	T7770E1023		✓		✓		✓	✓	3 position	
	TR23-F5	T7770F1005		✓		✓		✓	✓	5 position	
	KNOB-C	N/A		N/A	N/A	N/A	For use on TR23	N/A	N/A	N/A	Replacement Knob (C°)
	KNOB-F	N/A		N/A	N/A	N/A	For use on TR23	N/A	N/A	N/A	Replacement Knob (F°)
	KNOB-O	N/A		N/A	N/A	N/A	For use on TR23	N/A	N/A	N/A	Replacement Knob +/-
	C7772A1004	N/A		20K ohms non-linear	✓						No Honeywell logo
C7772A1012	N/A	20K ohms non-linear		✓						With Honeywell logo	

	Model Number	Sensor Type		Selectable Setpoint Adjustment 55° to 85°F, 13° to 30°C or Relative (- to +)	Occupied Override	Comments
	Honeywell TR20 Wireless Sensor	Temp	Humidity			
Wireless Temperature and Humidity Sensors*	TR21-WK	✓				Includes one prebound sensor and receiver.
	TR21-WKU	✓				Includes one prebound sensor and receiver. No Honeywell logo.
	TR23-WK	✓		✓	✓	Includes one prebound sensor and receiver.
	TR23-WKU	✓		✓	✓	Includes one prebound sensor and receiver. No Honeywell logo.
	TR21-WS	✓				Sensor only. For replacement. Requires a wireless receiver.
	TR23-WS	✓			✓	Sensor only. For replacement. Requires a wireless receiver.
	WRECVR					Wireless receiver only. For replacement. Requires a wireless sensor.

* Compatible controllers include Spyder, Stryker, CIPer and non-Honeywell controllers with remote setpoint. Compatible thermostats include T7350, T7351, TB8575 thermostats and non-Honeywell thermostats with remote setpoint.

	Part Number	Sensing Element	Description	Temperature Range	Use With
T775	50021579-001	1097 ohms at 77° F	Standard temperature probe	-40° to 350° F (-40° to 177° C)	All T775 Series 2000 models
	T775-SENS-WR		Water-resistant probe with 5-ft. leads	-40° to 270° F (-40° to 132° C)	
	T775-SENS-WT		Water-tight probe with 6-ft. leads	-40° to 158° F (-40° to 70° C)	
	T775-SENS-OAT		Outdoor air temperature sensor	-40° to 250° F (-40° to 121° C)	
	T775-SENS-STRAP		Strap-on	-40° to 350° F (-40° to 177° C)	
	C7031D2003	1097 ohms at 77° F	5-in. immersion sensor with wiring box (well included, 50001774-001)	-40° to 250° F (-40° to 121° C)	
	C7031B2005		6-in duct with wiring box	40° to 180° F (4° to 82° C)	
	C7031J2009		12-in. duct averaging sensor with four elements with wiring box	40° to 150° F (4° to 66° C)	
	C7046D1008		8-in. duct probe with mounting flange	40° to 220° F (4° to 104° C)	
	C7100D1001		12-in. flat response, duct averaging sensor with flange	-40° to 100° F (-40° to 38° C)	
	C7130B1009		Room mount sensor	-40° to 250° F (-40° to 121° C)	
	C7170B1000		3/8-in. diameter temperature probe		




T775-SENS-OAT



T775-SENS-WR



T775-SENS-WT



50021579-001



T775-SENS-STRAP



C7400S100

	Part Number	Sensing Element	Temperature Range	Insertion Length	Type	Mounting & Application
JADE Economizers	C7400S1000	Sylk Temperature & Humidity	-40° to 150° F (-40° to 66° C)	N/A*	Duct - Temp + Hum Sensor	Outdoor, return, discharge air sensor for Jade Economizer, LCBS, CIPer 30, Spyder Classic, Spyder model 5 and Stryker Controllers
	C7250A1001	20K NTC	-40° to 150° F (-40° to 66° C)	N/A*	Duct - Temp Sensor	Outdoor, mixed dry bulb sensor

GENERAL TEMPERATURE SENSORS



C7041B



C7041D



C7041J



C7041R



C7041F



C7041P



TB-WALL

	Part Number	Sensing Element	Resistance	Operating Range	Mounting and Application
Duct Mount	C7021B2005	10K ohms NTC Type II	10K ohms NTC at 77°F	-40° to 250° F	6" duct w/wiring enclosure
	C7021B2013				12" duct w/wiring enclosure
	C7021C2003				18" duct w/wiring enclosure
	C7021J2007				12' duct averaging w/wiring enclosure
	C7021R2000				12' duct averaging flexible copper
	C7021R2018				24' duct averaging flexible copper
	C7776A1006				6" duct probe w/flange, 8.5 in stranded wire
	C7776A1040				6" duct probe w/flange, 6 ft plenum cable
	C7023B2005				10K ohms NTC Type III
	C7023B2013	12" duct w/wiring enclosure			
	C7023C2003	18" duct w/wiring enclosure			
	C7023J2007	12' duct averaging w/wiring enclosure			
	C7023R2000	12' duct averaging flexible copper			
	C7023R2018	24' duct averaging flexible copper			
	C7778A1006	6" duct probe w/flange			
	C7778A1040	6" duct probe w/flange, 6 ft plenum cable			
	C7041B2005	20K ohms NTC	20K ohms NTC at 77°F	-40° to 250° F	
	C7041B2013				12" duct w/wiring enclosure
C7041C2003	18" duct w/wiring enclosure				
C7041J2007	12 ft. Duct (Averaging) w/wiring enclosure				
C7041R2000	12 ft. Duct flexible copper (Averaging)				
C7041R2018	24 ft. Duct flexible copper (Averaging)				
C7770A1006	6" duct probe w/flange				
C7770A1040	6" duct probe w/flange and 6 ft. plenum rated cable				
C7046D1008	PT1000				1,097K ohms PTC at 77°F
C7100D1001	PT3000	3,484K ohms PTC at 77°F	40° to 220° F	13" duct (Averaging)	
C7100A1015					
C7100C1003					
C7046A1004	3K ohms NTC	3K ohms NTC at 77°F	40° to 150° F	8" duct w/flange	
C7046A1038				12" duct w/flange	
C7046C1000				8" duct discharge w/flange	
C7150B1004	22.8K ohms NTC	22.8K ohms NTC at 77°F	40° to 250° F	Duct (internal)	
C7046B1010				6" Zone (Discharge w/flange)	
C7100B1013				13" duct (Averaging)	
Water	C7021D2001	10K ohms NTC Type II	10K ohms NTC at 77°F	-40° to 250° F	6" w/wiring enclosure, use well 50001774-001
	C7021K2005	10K ohms NTC Type III	10K ohms NTC at 77°F		Strap-on pipe sensor with wiring enclosure
	C7023D2001				6" w/wiring enclosure, use well 50001774-001
	C7023K2005				Strap-on pipe sensor with wiring enclosure
	C7041D2001	20K ohms NTC	20K ohms NTC at 77°F		6" w/wiring enclosure, use well 50001774-001
C7041K2005	20K ohms NTC	20K ohms NTC at 77°F	-40° to 250° F	Strap-on with wiring enclosure	
C7021F2009				10K ohms NTC Type II	10K ohms NTC at 77°F
C7023F2009	10K ohms NTC Type III	10K ohms NTC at 77°F			
C7041F2006	20K ohms NTC	20K ohms NTC at 77°F			
Wall Mount	C7772F1004	10K ohms NTC Type II	10K ohms NTC at 77°F	45° to 99° F	Flush wall mount, without logo
	C7772F1012			45° to 99° F	Flush wall mount, with logo
	C7021P2004			-40° to 250° F	Small metal button sensor
	TB-WALL-1014			32° to 122° F	Wall sensor
	TB-WALL-OVR-1014	10K ohms NTC Type III	10K ohms NTC at 77°F	32° to 122° F	Wall sensor with override
	C7772G1004			45° to 99° F	Flush wall mount, without logo
	C7772G1012			45° to 99° F	Flush wall mount, with logo
	C7023P2004			-40° to 250° F	Small metal button sensor
	C7772A1004	20K ohms NTC	20K ohms NTC at 77°F	45° to 99° F	Flush wall mount/no logo
	C7772A1012			45° to 99° F	Flush wall mount/with logo
C7041P2004	-40° to 250° F			Small metal button sensor	
C7130B1009	PT1000			1,097 Ohms PTC at 77°F	-40° to 100° F
TR29 + SP3000-2	SP3000-2	3,484 ohms PTC at 77°F	-40° to 250° F	Wall mount	
Water/Air	C7021N2001	10K ohms NTC Type II	10K ohms NTC at 77°F	-40° to 250° F	Probe Sensor with 6' Lead
	C7023N2001	10K ohms NTC Type III	10K ohms NTC at 77°F		
	C7041N2020	20K ohms NTC	20K ohms NTC at 77°F		

NOTE: 20K ohms NTC sensors are used with Excel 10, 15, 50, 100 and 500. See controller product data sheets for details. PT1000 sensors are used with Excel 15, 100, 500, and 600. See controller product data sheets for details. PT3000 sensors are used on certain Excel and Microcell products. See controller product data sheets for details. 3K ohm NTC sensors are used on W7100, W7459, W7215, W7212 and all economizer modules. 10K ohms NTC Type II sensors are used with TB7600, TB7300, and TB7600 Series communicating thermostats. 10K ohms NTC Type III sensors are used with WEBs-AX I/O Modules.

GENERAL TEMPERATURE SENSORS

	Part Number	Sensing Element	Temperature Range	Insertion Length	Type	Mounting & Application
Other Temp Sensors	TR29 + SP3000-2	3,484 ohms PTC at 77° F	-40° to 100° F (-40° to 38° C)	N/A	Enclosure + Sensor	Wall mount
	C7130B1009	1,097 ohms PTC at 77° F	-40° to 100° F (-40° to 38° C)	N/A	Enclosure + Sensor	Wall mount

* May be used with Duct Mounting Kit- Part # 50053060-001

HUMIDITY AND DEW POINT SENSORS

	Part Number	Output Signal	RH Accuracy	Mounting & Application	Voltage Supply	Temp Sensor	Use With	Insertion Length							
Humidity and Temperature Sensors	H7725A2010	Selectable 4-20mA, 0-10Vdc, or 0-5Vdc	± 2% from 20-95% RH	Wall	18-40 VDC/ 18-28 VAC	20K ohm at 77° F	T7350, H775, XL50, XFC, W750B/C, W7753, W7760A/C, W7761, CIPer 30, Spyder Classic, Spyder model 5, Compact VAV and Stryker Controllers	7.5" - 'B' model only							
	H7725B2006			Duct											
	H7726A2020			Wall											
	H7726B2024			Duct											
	H7735A2012			Wall											
	H7735B2018			Duct											
	H7735C2015			Outdoor					± 3% from 20-95% RH	20K ohm at 77° F	T7350, H775, XL50, XFC, W750B/C, W7753, W7760A/C, W7761, CIPer 30, Spyder Classic, Spyder model 5, Compact VAV and Stryker Controllers	7.5" - 'B' model only			
	H7736A2022			Wall											
	H7736B2026			Duct									1097 ohm at 77°F	Excel 15, Excel 10, T7350, T775 Series 2000, CIPer 30, Spyder Classic, Spyder model 5, Compact VAV and Stryker Controllers	7.5" - 'B' model only
	H7655A1001			0-10 VDC FIXED									5%	Wall	16-40 VDC/16-30 VAC



H77 Series Wall Mount



H77 Series Duct Mount



H77 Series Outdoor Mount



H7655A



HSS-DPS

	Part Number	Output	Switch	Hysteresis
Dew Point Sensors	HSS-DPS	Potential-free relay with changeover contact	RH > 90% ± 3% contact open; RH < 90% ± 3% closed	5% RH

IAQ SENSORS



C7262A



C7355A1050

	Part Number	Type	Output Signal	Display Screen	Mounting
IAQ Sensors	C7232A1008	CO2	0/2 - 10VDC or 0/4 - 20 mA w/ one adjustable SPST relay output	Yes	Wall
	C7232A1016	CO2		No	
	C7232B1006	CO2		Yes	Duct
	C7232B1014	CO2		No	(8" insertion length)
	C7262A1008	CO2		Yes	TR20 Series
	C7262A1016	CO2		No	Style Wall
	C7363A1017	PM2.5	4-20mA, 0-5/10VDC	No	Wall
	C7364A1016	TVOC	4-20mA, 0-5/10VDC, 3-step	No	Wall
	C7364B1014	TVOC		No	Duct
	C7355A1050	Temp, Hum, CO2, TVOC, PM2.5		No	Wall
	C7355B1052		RS485/RTU (Modbus)	No	Duct

NOTE: 20K ohms NTC sensors are used with Excel 10, 15, 50, 100 and 500. See controller product data sheets for details. PT1000 sensors are used with Excel 15, 100, 500, and 600. See controller product data sheets for details. PT3000 sensors are used on certain Excel and Microcell products. See controller product data sheets for details. 3K ohm NTC sensors are used on W7100, W7459, W7215, W7212 and all economizer modules. 10K ohms NTC Type II sensors are used with TB7600, TB7300, and TB7600 Series communicating thermostats. 10K ohms NTC Type III sensors are used with WEBS-AX I/O Modules.

CURRENT SENSORS



MCS



CSP

	Model Number	Trip Point	Core Type	Max. Current	Application
Current Switches	MCS-NO-A-50A	Adjustable, 0.75-50FLA	Micro-Solid	50A	Standard
	CS-NO-F-50A	Fixed, 0.25A	Solid	50A	Standard
	CS-NO-A-50A	Adjustable, 0.75-50FLA	Split	50A	Standard
	CSP-NO-A-50A	Adjustable, 0.45-50FLA	Split	50A	Standard
	CSP-NO-A-100A	Adjustable, 0.50-100FLA	Split	100A	Standard
	CSP-NO-A-150A	Adjustable, 0.50-150FLA	Split	150A	Standard
	CSP-NO-F-200A	Fixed, 0.35A	Split	200A	Standard
	CSP-NO-AVFD-150A	Automatically detected above 40 Hz	Split	150A	VFD Controlled Motor
	CSP-NO-AECM-200A	Adjustable, 0.25-3A Trip	Split	200A	ECM - Electronically Commutated Motor



CTP

	Part Number	Output Signal*	Selectable Ranges	Max Current	Core Type
Current Transmitters	CTP-5V-20A	0-5VDC	5/10/20A	100 A	Split
	CTP-10V-120A	0-10VDC	30/60/120 A	200 A	
	CTP-10V-200A	0-10VDC	Fixed 200A	200 A	
	CTP-A-20A	4-20mA	5/10/20A	200 A	
	CTP-A-120A	4-20mA	30/60/120 A	200 A	

*Note: 0 - 5/10 Vdc output (induced power) 4-20 mA output (12-30 Vdc power source required)



CR

	Part Number	Coil Rating	Contact Type/Rating
CR Relays	CR-24V-NO-10A	24VAC/DC, 15mA nom	N.O. / 10A @ 125VAC
	CR-24V-NC-10A	24VAC/DC, 15mA nom	
	CR-12VDC-NO-10A	9-12VDC, 30mA nom	
	CR-12VDC-NC-10A	9-12VDC, 30mA nom	

PRESSURE SENSORS



P7660



P7645

	Product Numbers	Configuration	Pressure Range	Output	LCD Display	Probe	
Dry Pressure Sensors	P7645C0010X	Panel/DIN Rail	0-0.10 "W.C.	4-20 mA Loop	No	No	
	P7645C0025X	Panel/DIN Rail	0-0.25 "W.C.				
	P7645C0100X	Panel/DIN Rail	0-1.0 "W.C.				
	P7645C0500X	Panel/DIN Rail	0-5.0 "W.C.				
	P7660P0500D	Panel/DIN Rail	0.1/0.25/2.5/5 "W.C.	Universal	Yes	No	
	P7660P0500X	Panel/DIN Rail	0.1/0.25/2.5/5 "W.C.		No		
	P7660P1000D	Panel/DIN Rail	1.0/2.5/5/10 "W.C.		Yes		
	P7660P1000X	Panel/DIN Rail	1.0/2.5/5/10 "W.C.		No		
	P7660D0500D	Duct/Panel/DIN Rail	0.1/0.25/2.5/5 "W.C.		Yes		Yes
	P7660D0500X	Duct/Panel/DIN Rail	0.1/0.25/2.5/5 "W.C.		No		
	P7660D1000D	Duct/Panel/DIN Rail	1.0/2.5/5/10 "W.C.		Yes		
	P7660D1000X	Duct/Panel/DIN Rail	1.0/2.5/5/10 "W.C.		No		



PWTA with conduit



PWTA with plenum cable



PWTA with armoured cable

	Part Number	Max PSIG	Selectable PSID Ranges	Cable Type	Cable Length (Feet)
Wet Pressure Sensors	PWTA40-X	40 PSIG	10/20/40 PSID	Conduit	—
	PWTA100-X	100 PSIG	50/75/100 PSID	Conduit	—
	PWTA250-X	250 PSIG	75/150/250 PSID	Conduit	—
	PWTA40-PC-9	40 PSIG	10/20/40 PSID	Plenum	9
	PWTA100-PC-9	100 PSIG	50/75/100 PSID	Plenum	9
	PWTA250-PC-9	250 PSIG	75/150/250 PSID	Plenum	9
	PWTA40-PC-50	40 PSIG	10/20/40 PSID	Plenum	50
	PWTA100-PC-50	100 PSIG	50/75/100 PSID	Plenum	50
	PWTA250-PC-50	250 PSIG	75/150/250 PSID	Plenum	50
	PWTA40-AC-9	40 PSIG	10/20/40 PSID	Armored	9
	PWTA100-AC-9	100 PSIG	50/75/100 PSID	Armored	9
	PWTA250-AC-9	250 PSIG	75/150/250 PSID	Armored	9
	PWTA40-AC-50	40 PSIG	10/20/40 PSID	Armored	50
	PWTA100-AC-50	100 PSIG	50/75/100 PSID	Armored	50
	PWTA250-AC-50	250 PSIG	75/150/250 PSID	Armored	50

For more information

BuildingControls.Honeywell.com

Honeywell Building Technologies

715 Peachtree St NE
Atlanta, Georgia 30308
honeywell.com

63-9285_LM | 11/20
© 2020 Honeywell International Inc.

**THE
FUTURE
IS
WHAT
WE
MAKE IT**

Honeywell